PB82-220856

Addendum/Supplemental Information for Valley CRSTER ISC

(U.S.) Environmental Protection Agency
Research Triangle Park, NC

Dec 80

U.S. Department of Commerce
National Technical Information Service
NTIS

EPAAQP

PB82-220856

DECEMBER 1980

ADDENDUM/SUPPLEMENTAL INFORMATION FOR VALLEY CRSTER ISC

The attached information on three models is furnished as part of the UNAMAP (Version 4) package to enable users to update their user's guides for these three models. The coding changes mentioned in this information have already been made to the source codes included as part of the UNAMAP (Version 4) tape.

MODELING SUPPORT SECTION
MAIL DROP 14 (919) 541-5335
OFFICE OF AIR QUALITY PLANNING AND STANDARDS
ENVIRONMENTAL PROTECTION AGENCY
RESEARCH TRIANGLE PARK, NC 27711

REPRODUCED BY
NATIONAL TECHNICAL
INFORMATION SERVICE
U.S. DEPARTMENT OF COMMERCE
SPRINGFIELD, VA. 22161

ATTENTION

AS NOTED IN THE NTIS ANNOUNCEMENT,
PORTIONS OF THIS REPORT ARE NOT LEGIBLE.
HOWEVER, IT IS THE BEST REPRODUCTION
AVAILABLE FROM THE COPY SENT TO NTIS.

December 1980

ADDENDUM/SUPPLEMENTAL INFORMATION

TO THE

VALLEY MODEL

The computer code modifications addressed herein are the complete set of changes made to date in the Valley Model code as it appears in the Valley Model User's Guide, EPA-4/2-77-018, September 1977. All modifications have been incorporated in the Valley code as part of the UNAMAP-4 available from the National Technical Information Service.

Each item in this report is preceded by the date on which it was issued. MAIN designates the main program.

A. Computer Program Modifications

Make the following modifications to Appendix B of the Valley Model User's Guide. Note that the code line sequence numbers in the Subroutine EBPLT1 code of UNAMAP are 100 larger than those in the User's Guide; the latter are cited herein as in the original source code in the User's Guide.

1. 8/78 - Insert the following line of code in MAIN:

```
      IF(TEMP.EQ.0.)TEMP=293.                                    MA02125
```

The original code caused all concentrations to be zero when conversion to standard conditions was specified.

2. 8/78 - Delete the following lines of code from Subroutine EBPLT1:

```
      P=1.E+10                                                   PL02370
      TEMP=1.E+10                                                PL02380
```

The original code caused the ambient temperature and pressure to be incorrectly assigned very large values for the analyses of the second and successive STAR decks in a single execution of the program, resulting in concentrations that are obviously in error.

3. 7/79 - Replace lines MA046200 through MA046600 in MAIN with the following lines of code:

```
      DUM3=-.5*((-H-DUM1)/SIGZ)**2                                    MA04615
      DUM4=-.5*((H-DUM1)/SIGZ)**2                                     MA04615
      IF(DUM4.LT.-40.)GO TO 68                                        MA04616
      IF(DUM3.LT.-40.)GO TO 64                                        MA04616
      DUM2=EXP(DUM3)+EXP(DUM4)                                        MA04617
      GO TO 65                                                        MA04617
   64 DUM2=EXP(DUM4)                                                  MA04618
```

This change precludes underflow diagnostics that may occur in some comput systems, but does not affect resulting concentrations.

4. 10/79 - Insert the following lines of code in MAIN:

```
      NPASS=0                                                         MA00850
      SGRID=0                                                         MA00851
      IF(GRID.EQ.SGRID.OR.NPASS.EQ.0.OR.SUM.EQ.0.0) GO TO 72          MA01384
      WRITE(6,71)                                                     MA01384
   71 FORMAT('1'/////// VALLEY DIAGNOSTIC.'/' BE AWARE THAT YOU HAVE CHMA01385
     AANGED THE VALUE OF GRID BELOW.'/' A RERUN IS REQUIRED UNLESS ALL RMA01385
     BECEPTORS OF CONCERN '/' LIE ON AN ELEVATED, FLAT PLANE.')       MA01386
   72 NPASS=1                                                         MA01386
      SGRID=GRID                                                      MA01387
```

These additions produce a warning of potential errors due to a possible oversight by the user. See page 3-2 (Section 3.1.4, first paragraph) of the Valley Model User's Guide.

5. 10/79 - Change the following line of code in MAIN to read:

```
      IF(MWT.NE.0.0) GO TO 3220                                       MA02070
```

6. 10/79 - In code line PL002500 of Subroutine EBPLT1 replace the literal data (i.e., ' VIA VALLEY V1') with 'VIA VALLEY V1 10/79'.

7. 10/79 - Insert the following line of code in EBPLT1:

```
      REAL MWT                                                        MA00075
```

8. 10/79 - Change the following code line of MAIN to read:

```
      IF(IZBRIG.EQ.0) GO TO 15                                        MA04120
```

Precludes division overflow in Subroutine BEH072.

9. 10/79 - Change the following lines of code in Subroutine EBPLT1 to read:

```
  803 FORMAT(T9,'HLIFE=',F6.2,'HRS. (etc.)                            PL01150
      IF(W.EQ.0.0) W=1.E10                                            PL01330
```

10. 10/79 - Insert the following lines of code in Subroutine EBPLT1:

```
      IF(TS(NSOR).EQ.1.E10) TS(NSOR)=0.                                PL014750
      IF(D(NSOR).EQ.1.E10) D(NSOR)=0.                                  PL014751
      IF(VS(NSOR).EQ.1.E10) VS(NSOR)=0.                                PL014752
      IF(VF(NSOR).EQ.1.E10) VF(NSOR)=0.                                PL014753

      DO  11540 I=1,ISOR                                               PL016950
      IF(GT(I).EQ.1.E10) GT(I)=0.                                      PL016951
      IF(TS(I).EQ.1.E10) TS(I)=0.                                      PL016952
      IF(D(I).EQ.1.E10) D(I)=0.                                        PL016953
      IF(VS(I).EQ.1.E10) VS(I)=0.                                      PL016954
      IF(VF(I).EQ.1.E10) VF(I)=0.                                      PL016955
11540 CONTINUE                                                         PL016956
```

These changes preserve the proper values of the variables examined under two constraints: (1) more than one stability/wind (STAR) array is evaluated in a single job; and (2) the source-data records are, for convenience, input only once for the entire job. Without the recommended changes, concentrations for the second and successive STAR data sets are significantly underestimated -- only under the constraints just mentioned. The revised program code should be used to reexamine the second and successive STAR data sets evaluated in a single job with the original program code when DUPSOR, an input control parameter, was assigned a value greater than zero.

11. The following set of program changes must be made as a group.

12/80 - Delete the following lines of code from MAIN:

```
      SIGZ=SQRT((A(LL)*ABS(XP)**B(LL)+C(LL))**2 + SIGI**2)             MA040500
      IF(IZBRIG.EQ.0)GO TO 15                                          MA041200
      IF(L.LT.5) GO TO 14                                              MA041300
      H=HS+BRIG                                                        MA042000
```

12/80 - Change the following lines of code in MAIN to read:

```
     C ISOR,GT,HST,WT,VFORM,AXDIR,IUR,ISHORT,NN,MAP,RECHT,HFCTR,K,P,MWT,MA001900
     A HLIFE,ISHORT,IBID,I26,IFR                                       MA010500
   73 FORMAT(F5.1,F7.0,F6.0,5I3,2F4.0,I3,3I1)                          MA010600
     * TS(IL),VS(IL),D(IL),VF(IL),IT,1.0,XXP,DTDZ(IT),TEMP,P,I26)      MA034000
CC  SIGMA IS INCREASED FOR ALL LOW-LEVEL SRCS XCPT FOR RURAL STABLE.   MA040300
     * TS(IL),VS(IL),D(IL),VF(IL),L,WS,XXP,DTDZ(L),TEMP,P,I26)         MA041700
```

12/80 - Replace the subroutine name "BEH072" with "BEHVAL" in lines MA033900 and MA041600 of MAIN.

12/80 - Insert the following lines of code in MAIN:

```
CC  1280 - OPTIONS ADDED FOR BUOYANCY INDUCED DISPERSION VIA SUM OF     MA000070
CC  SQUARES OF PG SIGMA AND (DELTA H/3.5), AND FOR FACTOR 2.6 OR 2.4 IN MA000080
CC  STABLE PLUME RISE(FINAL) FORMULA, AND FOR SELECTIVE EXCLUSION OF    MA000090
CC  TRANSITIONAL PLUME RISE.  P AND T CHANGED FOR PPM.                  MA000091
     D IBID,I26,IFR                                                     MA001910
CC  IBID = 0 NO BUOYANCY-INDUCED DISPERSION.                            MA013710
CC       = 1 VALLEY WITH BUOYANCY-INDUCED DISPERSION.                   MA013720
CC  I26  = 0 MODEL USES 2.4 IN STABLE PLUME RISE EQ                     MA013730
CC         1 MODEL USES 2.6 IN STABLE PLUME RISE EQ                     MA013740
CC  IFR  = 0 TRANSITIONAL PLUME RISE AVAILABLE FOR ALL STABILITIES.     MA013750
CC       = 1 NO TRANSITIONAL PLUME RISE.                                MA013751
CC       = 2 TRANSITIONAL RISE AVAILABLE FOR STABLE ONLY.               MA013752
    IF(IFR.GT.0)XXP=0.                                                  MA033711
    IF(XXP.EQ.0.)BRIGUN(IL)=DUM5                                        MA034110
      IF(IBID.EQ.0)GO TO 800                                            MA040410
      SIGZ=((A(LL)*ABS(XP)**B(LL)+C(LL))**2 + SIGI**2)                  MA040420
      GO TO 9                                                           MA040430
  800 SIGZ=SQRT((A(LL)*ABS(XP)**B(LL)+C(LL))**2 + SIGI**2)              MA040440
      IF(IZBRIG.EQ.0.AND.IBID.EQ.0) GO TO 15                            MA041110
      IF(IZBRIG.EQ.0.AND.IBID.NE.0) GO TO 802                           MA041120
      IF(L.LT.5.AND.IBID.EQ.0) GO TO 14                                 MA041130
      IF(L.LT.5.AND.IBID.NE.0) GO TO 804                                MA041140
      XXP=XP/1000.                                                      MA041535
      IF(IFR.EQ.1)XXP=0.                                                MA041540
      IF(XXP.EQ.0.)BRIG=DUM5                                            MA041750
      IF(IBID.NE.0)GO TO 802                                            MA041910
      H=HS+BRIG                                                         MA041920
      GO TO 15                                                          MA041930
  804 BRIG=BRIGUN(IL)/WS                                                MA041940
  802 IF(G.GT.0.0)BRIG=G                                                MA041950
      H=HS+BRIG                                                         MA041960
      DUM=BRIG/3.5                                                      MA041970
      DUM=DUM*DUM                                                       MA041980
      SIGZ=SQRT(SIGZ+DUM)                                               MA041990
```

12/80 - Change the following lines of code in Subroutine EBPLT1 to read:

```
      DIMENSION TS(50),VS(50),D(50),VF(50),RECHT(112),KFIRI(8),NFIRI(8) PL000900
      DIMENSION VERBL (12),URBRUR(2),THREED(12),KBID(8),KCON(8),KBLK(8) PL001000
     C ISOR,GT,HST,WT,VFORM,AXDIR,IUR,ISHORT,NN,MAP,RECHT,HFCTR,K,P,MWT,PL001600
     C T27,F5.1,T93,F5.1,'          VALLEY          '/T2,'1280',        PL002500
     L T42,F5.1,T78,F5.1,/T5,8A4,T56,'0 KM',3X,F7.3,5('KM ',F7.3),'KM'/ PL005200
     M T5,8A4,T56,6('].....+.....'),']'/T5,8A4,T60,F5.1,                PL005300
     G V(68),V(54),V(77),V(49),V(61),V(69),V(55),(KFIRI(I),I=1,8),      PL014500
     G S(68),S(54),S(77),S(49),S(61),S(69),S(55),(KFIRI(I)=1,8),        PL021700
```

12/80 - Insert the following lines of code in Subroutine EBPLT1:

```
      D IBID,T26,IFR                                                          PL001610
       DATA KCON/'BRIG','GS S','TABL','E CO','NSTA','NT I','S 2.',           PL002150
      A         '6.  '/                                                     PL002155
       DATA KBID/'BUOY','ANCY','-IND','UCED',' DIS','PERS','ION.',           PL002160
      A         '    '/                                                     PL002165
       DATA KBLK/'    ','    ','    ','    ','    ','    ','    ',         PL002170
      A         '    '/                                                     PL002175
       DATA KFIRI/'FINA','L RI','SE O','NLY',',' FOR',' ALL',' CAS',        PL002176
      A          'ES. '/                                                    PL002177
       DATA NFIRI/'ONLY',' FIN','AL R','ISE ','FOR ','NONS','TABL',         PL002178
      A          'E.  '/                                                    PL002179
       IF(IFR.EQ.1)GO TO 509                                                 PL010214
       IF(IFR.EQ.2)GO TO 502                                                 PL010215
       DO 501 I=1,8                                                          PL010216
       KFIRI(I)=KBLK(I)                                                      PL010219
  501 CONTINUE                                                               PL010222
       GO TO 509                                                             PL010225
  502 DO 503 I=1,8                                                           PL010228
       KFIRI(I)=NFIRI(I)                                                     PL010231
  503 CONTINUE                                                               PL010234
  509 CONTINUE                                                               PL010237
       IF(IBID.NE.0)GO TO 500                                                PL010250
       DO 510 I=1,8                                                          PL010255
       KBID(I)=KBLK(I)                                                       PL010260
  510 CONTINUE                                                               PL010265
  500 IF(I26.NE.0)GO TO 520                                                  PL010270
       DO 525 I=1,8                                                          PL010275
       KCON(I)=KBLK(I)                                                       PL010280
  525 CONTINUE                                                               PL010285
  520 CONTINUE                                                               PL010290
      * (SCALE(N1),N1=1,6),(KCON(I),I=1,8),(KBID(I),I=1,8),                   PL014550
      * (SCALE(N1),N1=1,6),(KCON(I),I=1,8),(KBID(I),I=1,8),                   PL021710
       DO 3805 I=1,8                                                         PL022450
       KCON(I)=KBLK(I)                                                       PL022451
       KBID(I)=KBLK(I)                                                       PL022452
       KFIRI(I)=KBLK(I)                                                      PL022453
 3805 CONTINUE                                                               PL022459
```

12/80 - Change the subroutine name "BEH072" to "BEHVAL" in Subroutine BEH072 line BE000100. This subroutine will hereafter be referred to as "BEHVAL."

12/80 - Change the following lines of code in Subroutine BEHVAL to read:

```
     1 KST,U,X,DTHDZ,T,P,I26)                                                 BE000200
       DHA = PRC*(F/(U*S))**0.333333                                          BE010300
```

12/80 - Insert the following lines of code in Subroutine BEHVAL:

```
C  BEHVAL - BEH072 WITH OPTION TO PERMIT 2.4 OR 2.6 AS COEFFICIENT       BE000298
C  IN STABLE FINAL PLUME RISE EQN.  X =0 FORCES FINAL RISE, AS IN BEH072 BE000299
      PRC=2.4                                                           BE005150
      IF(I26.NE.0)PRC=2.6                                               BE005151
```

These changes permit the user to optionally designate treatment of the effects of buoyancy-induced dispersion (BID), to designate whether the program will assign the constant coefficient in the final stable plume-rise equation a value of 2.4 or 2.6, and to designate conditions for the use of transitional plume rise. See Section B below for discussion of the options. They also allow for the continued identification of the revisions made to the Valley Model computer code.

The use of the optional constants for the plume-rise formula are self-explanatory. Briggs' latest recommendation is to assign the constant a value 2.6.

Default is zero in all cases, and such default relegates the analysis to that controlled by the original Valley code. Statements are printed in the output indicating when the new options have been invoked.

12. Make the following modifications to MAIN:

12/80 - In statement MA009000 delete "OR TO PPM."

12/80 - In statement MA009300 change "CHI IS AT AMBIENT COND." to "CHI (UG/M3 ONLY) IS AT AMBIENT COND."

12/80 - In statement MA012300 change "TEMP/(MWT*P)" to "298./(MWT*1013.2)".

12/80 - Delete statements MA012400 and MA012600.

12/80 - Change the following line of code to read:

```
      ALWT=8.31E04*298./(MWT*1013.2)                                    MA021900
```

These modifications describe and assure the proper values of temperature and pressure used in the conversion from $\mu g/m^3$ to ppm. Concentrations in ppm generated by the original computer code can be in error by up to about + 15 percent in rare cases, but most often the error would be near zero.

13. 12/80 - Change the following lines of code in Main to read:

```
 3420 IF(PLHT.GT.0.0) GO TO 3430                                        MA043500
      IF(PLHT.LE.-400.0) GO TO 99                                       MA043700
      WS=WS*(400./(400.+PLHT)                                           MA043800
 3430 IF(PLHT.LT.10.0) PLHT=10.                                         MA044000
```

These changes eliminate insignificant positive errors in calculated concentrations. The largest of these errors occurred at receptors no more than 10 m below the undisturbed plume centerline elevation.

B. Text Corrections to the Valley Model User's Guide

1. 8/78 - Page 3-2, line 5: Change 293 to 298.

2. 10/79 - The discussion of lateral plume deflection on Page 2-2, last paragraph, is incomplete. A statement to further define the treatment of emissions from very low heights during stable conditions is as follows: "The height-dependent attenuation factor for concentrations on elevated terrain is not applied to contributions from any stable plume with an undisturbed height of 10 m or less above stack base."

3. 10/79 - Page 3-1, Section 3.1.1, insert the following:

   No attempt should be made to force alignment of the printed concentrations exactly on 16-point radials from map center or exactly on circles about map center. Consider, for example, the first printed concentration from center about the southwest direction. The decimal point lies 9.8 print spaces from center at a bearing of 227.5 degrees from center (using graphical techniques). With the variable GRID equal to 100 m, the distance of this receptor from center of the plot is 980 m. This receptor does not lie exactly on the southwest radial (225 degrees), nor does it lie on a circle about center that passes through, say, the first receptor to the west of center. The latter lies 8 print spaces from center, or, for this example, 800 m from center. Hence, the printed concentration decimal point represents, without relocation, the geographical position of a receptor in the real world.

4. 12/80 - Page 1-9, add the following lines to the list in Section 1.4.4:

   - BUOYANCY-INDUCED DISPERSION
   - COEFFICIENT 2.4 OR 2.6 IN FINAL STABLE PLUME-RISE EQUATION
   - TRANSITIONAL AND/OR FINAL PLUME RISE

5. 12/80 - Page 2-4, Equation 2.1, and page 2-7, Equation 2.1a:

   Change h to h_o.

6. 12/80 - Page 2-5, last line: Change

   "T/(MP)" to "298./(M·1013.2)".

7. 12/80 - Page 2-6: Delete lines 2 and 4 (i.e., definitions of T and P).

   12/80 - Page 2-8, last line of Section 2.1.3: Delete "during $S \leq 4$" and insert "except that SIGI is set to zero during stable conditions in the rural mode. The vertical dispersion coefficient can be adjusted internally, at the user's discretion, for buoyancy-induced dispersion so that the net coefficient becomes

$$\sigma_z = \{(ax_p^b + d)^2 + SIGI^2 + (\Delta h/3.5)^2\}^{1/2}$$

   where Δh is either the calculated or user-assigned plume rise at the receptor of concern."

9. 12/80 - Page 2-8, next to last line: Insert as a reference "1975." Also, add to list of references on page 5-1 the following paper by Briggs:

   _____, 1975: Plume Rise Predictions. Lectures on Air Pollution and Environmental Impact Analysis. September 29 - October 3, 1975, Boston, Massachusetts. D. A. Haugen, Workshop Coordinator. AMS, Boston. pp59-104.

10. 12/80 - Insert the following at bottom of page 2-8:

    The user may designate a value of 2.4 or 2.6 for the constant coefficient in the final plume rise equations for stable conditions. The value 2.6 is consistent with other EPA models. The user also selects one of three techniques which cause the program to invoke the use of : (1) the original code, which selects the lesser plume rise from the transitional and final rise formulae for all stabilities; or (2) only the final rise formula for all stabilities; or (3) only the final rise formula for nonstable conditions and the lesser result from both formulae for stable conditions. The second of these three techniques affords consistency with other EPA models; the third may be preferred for sources near elevated receptors.

11. 12/80 - Page 2-12, line 3: Delete "made."

12. 12/80 - Page 2-14, replace lines 8 through 12 with the following:

    cloudy conditions, and can exist in both the daytime and nighttime. In rural areas the afternoon mixing height is halved in the Valley Model, and in urban areas it is averaged with the nighttime mixing height, for 40 percent of the class S = 4 occurrences. The remaining 60 percent of the neutral class (urban or rural) utilizes the mean afternoon mixing

13. 12/80 - Page 2-16, seventh line from bottom, delete the phrase "for the long-term option only,"

14. 12/80 - Page 3-9, last line, add the following:

    An input value of zero (or blank) in effect defaults to infinity for the calculations, and is printed as 999.99 in the output.

15. 12/80 - Page 4-15, in @HDG card, replace the comma between X and M with a period.

December 1980

ADDENDUM/SUPPLEMENTAL INFORMATION

TO THE

USER'S MANUAL FOR SINGLE SOURCE (CRSTER) MODEL

The computer code modifications addressed herein are the complete set of changes made to date to the CRSTER code as it appears in the User's Manual for Single-Source (CRSTER) Model, EPA-450/2-77-013, July 1977. All modifications have been incorporated in the CRSTER code as part of the UNAMAP-4 available from the National Technical Information Service (NTIS).

Each item in this report is preceeded by the date on which it was issued.

A. 9/79 - Additional Options

Several options have been added to the CRSTER computer program. These options potentially make the model more useful for a variety of applications. However, please note that the inclusion of the options does not constitute a change in the recommended procedures. The options are therefore to be exercised for regulatory applications only with the concurrence of the appropriate Regional Office.

The following list identifies the options that have been added to the CRSTER program:

- transitional plume rise
- anemometer height input
- wind profile power-law exponent input
- stack downwash
- momentum plume rise

The new namelist variables associated with these options are as follows:

Variable Name	Type	Description
IPLAS	Integer	0 = Transitional plume rise not accounted for. 1 = Transitional plume rise accounted for. Default = 0 Current recommended usage: IPLAS = 0
ANHT	Real	Anemometer height. Default = 7. meters. Current recommended usage: ANHT = Actual anemometer height.

IDWN	Integer	0 = Stack downwash <u>not</u> accounted for. 1 = Stack downwash accounted for. Default = 0 Current recommended usage: IDWN = 0
P	Real	Array of dimension 6. Positions 1-6 correspond to the set of wind profile law exponents as a function of stability. Default = .1, .15, .2, .25, .3, .3 Current recommended usage: P = Default values
IMOM	Integer	0 = Momentum plume rise not accounted for. 1 = Momentum plume rise accounted for. Default = 0 Current recommended usage: IMOM = 0

The momentum plume rise option allows the momentum plume rise equations to be used for cold plume sources. This option has no effect for sources with buoyant plumes - the sources for which CRSTER was originally designed to be used. Hence, the default for this option is to omit the momentum plume rise equation. However, since it may be necessary to consider sources with non-buoyant plumes, the option which includes the momentum plume rise equations may be used for such cases.

9/79 - Program Modifications Required to Incorporate Additional Options

I. Replace the following lines of code:

MAIN CRSV

```
*Q240(12,20),V240(12,20),T240(12,20),ANHT,P(6),IPLAS,IDWN,IMOM          CV001300
*ISC,SC1,SC3,SCN,SC24,SCAN,ANHT,P,IPLAS,IDWN,IMOM                       CV001700
```

SUBROUTINE CRS

```
 DIMENSION DTH(11),SYD(5,6),SZD(5,6),LOOP(6,2),                         CR000800
*TAPIN(171),JMAX3(4),CHI(180),HE(20,5),DDD(366)                         CR001200
*Q240(12,20),V240(12,20),T240(12,20),ANHT,P(6),IPLAS,IDWN,IMOM          CR001900
 WS(IS)=XWS*((HP(IS)/ANHT)**P(KST))                                     CR016400
 H=HE(IH,J)-FADJ                                                        CR021800
```

SUBROUTINE BLK

```
      Q240(12,20),V240(12,20),T240(12,20),ANHT,P(6),IPLAS,IDWN,IMOM     BL000400
```

II. Delete the following lines of code:

SUBROUTINE CRS

```
      DATA P/.1,.15,.2,.25,.3,.3/                                       CR002700
      HE(IS)=HEIS                                                       CR018500
```

III. Add the following lines of code:

MAIN

```
      IF(IPLAS.EQ.1)WRITE(6,841)                                          CV009110
  841 FORMAT(1X,'GRADUAL PLUME ASCENT UP TO POINT OF FINAL ',             CV009120
     1'RISE ACCOUNTED FOR')                                               CV009130
      WRITE(6,842)ANHT                                                    CV009140
  842 FORMAT(1X,'ANEMOMETER HEIGHT IS ',F4.1,' METERS')                   CV009150
      IF(IDWN.EQ.1)WRITE(6,843)                                           CV009160
  843 FORMAT(1X,'STACK DOWNWASH ACCOUNTED FOR')                           CV009170
      IF(IMOM.EQ.1)WRITE(6,844)                                           CV009180
  844 FORMAT(1X,'MOMENTUM PLUME RISE ACCOUNTED FOR')                      CV009185
      WRITE(6,845)P                                                       CV009190
  845 FORMAT(1X,'WIND PROFILE EXPONENTS ARE: ',6(F7.3,','))               CV009195
```

SUBROUTINE CRS

```
      IF(IDWN.EQ.0) GO TO 1779                                            CR018110
C***ACCOUNT FOR STACK DOWNWASH                                            CR018115
      DUD=VS(IS)/WS(IS)                                                   CR018120
      IF(DUD.LT.1.5)HPIS=HP(IS)+2.*D(IS)*(DUD-1.5)                        CR018130
      IF(HPIS.LT.0.)HPIS=0.                                               CR018140
 1779 CONTINUE                                                            CR018150
      IF(IMOM.EQ.0)GO TO 1801                                             CR018203
C***MOMENTUM PLUME RISE ACCOUNTED FOR                                     CR018206
      DELT=TSIS-T                                                         CR018209
      IF(KST.GT.4)GO TO 1802                                              CR018212
      VFIS=0.785398*VS(IS)*D(IS)*D(IS)                                    CR018215
      DUMF=3.12139*VFIS*DELT/TSIS                                         CR018218
      IF(DUMF.GE.55.)GO TO 1783                                           CR018221
      DTMB=.0297*TSIS*VS(IS)**0.333333/D(IS)**0.666667                    CR018224
      GO TO 1784                                                          CR018227
 1783 DTMB=.00575*TSIS*VS(IS)**0.666667/D(IS)**0.333333                   CR018230
 1784 CONTINUE                                                            CR018233
      IF(DELT.GE.DTMB)GO TO 1801                                          CR018236
      HEIS=HPIS+3.*VS(IS)*D(IS)/WSIS                                      CR018239
      GO TO 1803                                                          CR018242
```

```
 1802 CONTINUE                                                                  CR018245
      S=9.80616*DTHDZ/T                                                         CR018248
      DTMB=0.019582*T*VS(IS)*SQRT(S)                                            CR018251
      IF(DELT.GE.DTMB)GO TO 1801                                                CR018254
      DHA=3.*VS(IS)*D(IS)/WSIS                                                  CR018257
      DELHF=1.5*(VS(IS)*VS(IS)*D(IS)*D(IS)*T/(4.*TSIS*WSIS))**0.333333/         CR018260
     *S**0.166667                                                               CR018263
      IF(DHA.LT.DELHF)DELHF=DHA                                                 CR018266
      HEIS=HPIS+DELHF                                                           CR018269
 1803 CONTINUE                                                                  CR018272
      DO 1804 J=1,5                                                             CR018275
      HE(IS,J)=HEIS                                                             CR018278
 1804 CONTINUE                                                                  CR018281
      GO TO 1800                                                                CR018284
 1801 CONTINUE                                                                  CR018287
      IF(IPLAS.EQ.1)GO TO 1781                                                  CR018296
      DO 1780 J=1,5                                                             CR018410
      HE(IS,J)=HEIS                                                             CR018420
 1780 CONTINUE                                                                  CR018430
      GO TO 1800                                                                CR018440
C***ACCOUNT FOR TRANSITIONAL RISE UP TO POINT OF FINAL RISE                     CR018445
 1781 DO 1782 J=1,5                                                             CR018450
      RDIS=RNG(J)                                                               CR018460
      CALL BEH072(DUMHX,HEIS,DUMHMW,DUMF,DHA,DUMDSF,DUMDHX,                    CR018470
     *HPIS,TSIS,DUMVS,DUMD,VFIS,KST,WSIS,RDIS,DTHDZ,T,DUMP)                     CR018480
      HE(IS,J)=HEIS                                                             CR018490
 1782 CONTINUE                                                                  CR018495
```

SUBROUTINE BLK

```
      DATA P/.1,.15,.2,.25,.3,.3/                                               BL001500
      DATA ANHT/7./                                                             BL001600
      DATA IPLAS/0/                                                             BL001700
      DATA IDWN/0/                                                              BL001800
      DATA IMOM/0/                                                              BL001900
```

B. Computer Program Modifications

Several program modifications are described below. Some changes are cosmetic or produce a code more compatible with a variety of computer systems. Others may affect the output of the model slightly; however, the effect is of no consequence for applications in which CRSTER is most commonly used.

Make the following program line modifications to Appendix A of the User's Manual and check your computer programs for conformance.

PREPROCESSOR PROGRAM

1. 8/78 - In line METO3040 change ' Day ',I2, to ' DAY ',F4.0,.

2. 9/79 - Remove the statement number 220 from line METO2040.

3. 9/79 - Insert the following line of code:

```
      220 CONTINUE                                                    METO2041
```

SINGLE SOURCE CRSTER MODEL PROGRAM

1. 8/78 - Insert the following line of code:

```
      IF(ELEV(I7,I8).LT.PELEV)GADJ(I8,I7)=0.0                         CV022910
```

   The addition of this line of code will reposition the receptors that are below ground elevation of the plant to plant elevation. This prevents concentration estimates from being unrealistically low for receptors at elevations lower than the plant. This line of code was inadvertantly omitted from the original program.

2. 8/78 - Delete lines CV002000 and CV002100.

3. 8/78 - Insert the following lines:

```
      IMET=1                                                          CV002710
      IPTZ=0                                                          CV002720
```

4. 8/78 - Remove statement numbers 152, 816, and 515 respectively from lines CV013200, CV016400 and CV027700, and change the NS in line CV026400 to I2.

5. 8/78 - Remove IHC(4), from line CR000800.

6. 8/78 - Remove IHC, and 6,13,18,24, from line CR002700.*

7. 8/78 - Delete lines CR008600, CR068800, CR068900, CR071300 and CR071400.

*This modification is not required if the options under Section A herein are employed.

8. 8/78 - Insert a comma after:

   TABLE' in line CR045500,
   '/' in line CR061400,
   '/' in line CR061800 and
   CO' in line CR067000.

9. 8/78 - Remove ,KSTL from lines CV027700 and CR000100.

10. 8/78 - Remove TX3(2),TX4(2), from line BL000200.

11. 9/79 - Insert the following line of code:

```
      IF(KST.GE.5) GO TO 2350                                    CR023210
```

    4/80 - Change the following line of code to read:

```
      IF(CHEK.GE.1.6.AND.KST.LT.5)GO TO 2400                     CR022400
```

    12/80 - Change the following line of code to read:

```
      IF(KST.LT.5.AND.H.GT.XMH)GO TO 2800                        CR022000
```

    The addition/modification of these lines of code prevent inappropriate limited mixing under stable conditions in the rural mode. This may have a slight affect on concentrations for stable conditions; however this has no effect on design concentrations for applications in which CRSTER is most commonly used.

12. 9/79 - Change the following lines of code to read as follows:

```
C   BEH072   (BRIGGS EFFECTIVE HEIGHT)  September 79              BE000300
C    THIS DIFFERS FROM THE OCT. 1972 VERSION IN STATEMENT 24+1:    BE000400
C     THE CONSTANT 2.6 PREVIOUSLY WAS 2.4.                        BE000500
C                                                                 BE000600
       DHA  = 2.6*(F/(U*S))**0.333333                             BE010300
```

    The code in line BE010300 is the equation for plume rise for the stable case as it is currently recommended by Briggs*. The constant "2.6" represents a change from Briggs' previously recommended value of "2.4", which was used in the original CRSTER code. This change causes the plume rise under stable conditions to be somewhat greater; however, this has no effect on design concentrations for applications in which CRSTER is most commonly used.

*Briggs, Gary A., 1972: Discussion on Chimney Plumes in Neutral and Stable Surroundings. Atmos. Environ. 6, 507-510 (July 72)

13. 9/79 - Delete lines CR015700 and CR015800 and replace with the following five lines:

```
C***IF STABILITY=7,SET KST AND KSTL TO 6.                        CR015700
      IF(ISTAB(IHR).LT.7) GO TO 1631                             CR015800
      KST=6                                                      CR015810
      KSTL=6                                                     CR015820
 1631 CONTINUE                                                   CR015830
```

The replacement of these lines of code will effectively reset all stability class 7 values to 6 and calculate a concentration for the time period involved. Since CRSTER was originally designed for relatively tall stacks with hot plumes and since stability class 6 results in nearly zero ground level concentrations, CRSTER was originally coded to assign a zero for the occurrence of stability class 7. However, to maintain consistency with the RAM and MPTER models which have been designed to accommodate, in addition, low level sources for which the stable conditions of stability class 6 may produce significant concentrations, the calculation of concentrations in CRSTER for stability class 7 (extremely stable) conditions is necessary. This change, though, will have no effect on design concentrations for applications in which CRSTER is most commonly used.

14. 9/79 - Insert the following lines:

```
      DATA HV1,HVX,HV3,KV1,KVX,KV3/150*0.0,150*0/                CR002410
      IG=51-KIG                                                  CR031610
      IG=51-KIG                                                  CR036810
      IG=51-KIG                                                  CR042210
```

15. 9/79 - In lines CR031600, CR036800 and CR042200 change <u>IG=50,2,-1</u> to <u>KIG=1,49</u>.

16. 12/80 - Change the following lines of code to read as follows:

```
C--CRSTER--UNEVEN TERRAIN MODEL--REVISED-12/80                   CV000100
*'  EMISSION UNITS: GM/SEC  ', ' AIR QUALITY UNITS: GM/M**3 12/80')  CV003800
```

These modifications allow for the continued identification of the revisions made to the CRSTER computer code.

17. 12/80 - Change the following lines of code to read as follows:

```
     *HLH(2,24),WS(20),HP(20),TS(20),TITLE(20),IDENT(5),VF(20),D(20),  CR000600
     *TAPIN(123),JMAX3(4),CHI(180),HE(20,5),DDD(366)             CR001200
 8042 IF(IMET.EQ.0)GO TO 1199                                    CR012600
      WRITE(6,1500)TAPIN,((HLH(I,J),J=1,24),I=1,2)               CR012900
      XMH =HLH(IUR,IHR)                                          CR014500
```

12/80 - Delete lines CR011500 through CR012500

These modifications eliminate the need to restructure the mixing height arrays as read from the preprocessor file.

18. 12/80 - Delete the following line of code;

```
      IDIR=DIR/10.                                                    CR019100
```

12/80 - Add the following lines of code:

```
      IF(DIR.LT.0.0)IDIR=(DIR/10.)-0.005                              CR019110
      IF(DIR.GE.0.0)IDIR=(DIR/10.)+0.005                              CR019120
```

These modifications eliminate the possibility of calculating incorrect receptor directions due to computer hardware limitations which do not allow for the exact representation of whole numbers in decimal notation.

19. 12/80 - Insert the following lines of code:

```
      IVT3=0                                                          CR005010
      IVTV=0                                                          CR005020
```

12/80 - Change the following lines of code to read as follows:

```
8007  IVT3=IVT3+1                                                     CR035400
      IF(IVT2.NE.3)GO TO 8008                                         CR035500
      IVT3=0                                                          CR035600
      IVT1=IHR/3                                                      CR035700
```

12/80 - Delete lines CR035800 and CR035900

12/80 - Change the following lines of code to read as follows:

```
      CHIH=CHIH/3.0                                                   CR036500
8052  IVTV=IVTV+1                                                     CR040800
      IF(IVTV.NE.IVT)GO TO 8054                                       CR040900
      IVTV=0                                                          CR041000
      AVT=IVT                                                         CR041100
      IVT1=IHR/IVT                                                    CR041200
```

12/80 - Delete line CR041300.

These modifications eliminate the possibility of the 3-hour and variable hour counter being miscalculated due to computer hardware limitations which do not allow for the exact representation of whole numbers in decimal notation.

C. 8/78 - Input Form Correction

The format of the PREP INITIALIZATION CARDS form at the top of Figure C-1, PREPROCESSOR INPUT DATA CODING FORMS, page C-3, is in error and should be modified to be compatible with the format described in TABLE 4-1, PREPROCESSOR INITIALIZATION CARD FORMAT, on page 4-11 of the User's Manual.

D. 8/78 - Clarification of the Highest 50 Concentration Tables

Users should note that the highest 50 maximum daily concentration table allows only the highest of the 180 24-hour average receptor concentrations on each day to be a candidate for entry into the table. However, the highest 50 concentration tables for 1-hour, 3-hour and variable hour time periods allow all of the 180 receptor concentrations for the specified time period to be candidates for entry into their respective tables.

If one desires a high 50 maximum daily concentration table where all of the 180 receptor concentrations are candidates for entry, then the variable time option should be used. To accomplish this, the namelist variable IVT should be set equal to 24 and program line CV011600 on page A-13 should be modified to read:

```
(OR.IVT.EQ.12.OR.IVT.EQ.24)                    CV011600
```

E. 8/78 - Random Number Alternative

The preprocessor program requires a random number subroutine not supplied with the program. The subroutine calculates numbers to be used in the development of the hourly randomized wind flow vectors. However, the set of numbers in Appendix A of this Supplement should be used routinely. These numbers were used to derive the randomized wind flow vectors for the test case. They are the set used by EPA for regulatory applications. These numbers were computed by the Sperry Rand Corp. random number generator subroutine, RANDU, installed on EPA's UNIVAC 1110 computer; the random number seed used is 65549.

Each line of data in Appendix A contains the day number and 24 integers. The positions of the integers(1-24) identify the hours of that day for which the integers are to be used in the derivation of the randomized wind flow vectors. Using the numbers will require the user to effectively modify the preprocessor program such that the given integers get transferred into the integer variable IRAND in line MET01870 to properly coincide with the KHR hour of the IDY day.

F. 9/79 - Running Averages

A new subroutine has been developed for the purpose of calculating running averages. The subroutine, entitled RUN, has been written for the express use with the Single Source (CRSTER) Model. The use of the procedure is optional and allows for the selection of running 3-hour, 8-hour and/or 24-hour averaging times. For each averaging time selected the subroutine will produce a table of highest concentrations and a table of second highest concentrations for each of the 180 radial receptors defined. The second highest table values are determined using the criteria that there is one other non-overlapping value that is at least as high as the second highest value. This procedure is consistent with that stated in Issue 7B, OAQPS Guidelines for The Interpretation of Air Quality Standards, No. 1.2-008 (Revised February 1977). Also, for each averaging time selected a high-50 table will be produced. This table allows concentrations for different starting hours for the same day, direction and distance to be candidates for inclusion.

A note of caution, though, is in order for prospective users. Selection of all three averaging time options will cause an increase in the CRSTER model run time by approximately a factor of thirteen (13). Selection of one or two running averages will show proportionate increases.

Instructions for the installation and use of Subroutine RUN are given in the first 47 lines of code for the subroutine. The computer code can be found in Appendix B of this Supplement.

Appendix A

1	52877o971580736851814644
2	0660401304595314825698912
3	4084130328o2561435121351
4	00235o0201179654731313o2
5	9814696932232492301164z6
6	0797o026229059666692560o0
7	27497038487650198856z659
8	352919954431386324767248
9	900803784851894758053489
10	57492988065790022173962S
11	48787865o914981570380053
12	2380122675232253036901z4
13	32738417576541501840254z
14	87246068442175106097011z
15	46249436116484707156873z
16	0313866261566459053409z6
17	12387145860902862331225z
18	43379632761159593394357o
19	1190726o1583445782481520
20	37181792492074675319383z
21	34341531946930422803012z
22	65489616282711983091495z
23	41443531930843476985111z
24	03123617281231722666997z
25	4689590586527606405542414
26	69228070786006049582008z
27	56552514567401802500250o
28	14186103388029565224152z
29	16952878737475984171368z
30	9o17426916o3842765872552
31	82657196082018302303520z
32	72131030480083002603965z
33	69793700905070642821743z
34	59020046879422o119067279
35	11096213809771960698086z
36	0366303249669089719636z1
37	27402183822083966625361z
38	29825468872506455872949z8
39	45954659580786672391730z
40	38015201455830126113099S
41	93450953145o837928419815
42	07861072795526998157500z
43	3385367o0691252826946929
44	89318614358531434980332z
45	46002948772861977031522z
46	7o642158020926208009584z
47	95685394289679046368835z
48	0658519525982863382467z
49	77781448223101503748276z
50	33203241854766118164231z
51	27852769o176248021959004
52	48228280806857222568376z
53	04408494818038867520039z
54	02435795653009010096642z
55	76658103564359976888591z
56	89219767607004952521408z
57	5246947o3544250618789598
58	21769877935329990523092z
59	33014304103349636714396z

60	3321829628819989593333 74
61	9334490971125002407298 43
62	3237983278190077637062 59
63	4970201318407273887234 31
64	4401419508359845373802 81
65	0441454925246153530914 64
66	8650150502073624665324 94
67	6220682448547956388450 18
68	3726469460906848990021 12
69	3434153194693042280301 23
70	6548961628271198309149 57
71	4144353193084347698511 14
72	0312361728123172266699 73
73	4689590586527664055424 14
74	6922807078600604958200 82
75	5655251456740180250025 00
76	1418610338802956522415 22
77	1695287873747598417136 82
78	9617426916638427658725 52
79	8265719608201830230352 07
80	7213103048008300260396 56
81	6979370090507064282174 37
82	5902004687942261190672 79
83	1109621380977196069808 62
84	0366303249669089719636 81
85	2740218382208396662536 11
86	2982546887256455872949 78
87	4595465958078667239173 06
88	3801520145583012611309 95
89	9345095314568379284198 15
90	0786107279552699815750 08
91	3385367606912528269469 29
92	8931861435853143498033 20
93	4600294877286197703152 27
94	7664215802092620800958 48
95	9568539428967904636883 58
96	0658519525982886338246 70
97	7778144822310150374827 69
98	3320324185476611816423 12
99	2785276961762480219590 04
100	4822828080685722256837 60
101	0440849481803886752003 91
102	0243579565300901009664 27
103	7665810356435997688859 11
104	8921976760700495252140 88
105	5246947635442506187895 98
106	2176987793532999052309 21
107	3301430410334963671439 69
108	3321829628819989593333 74
109	9334490971125002407298 43
110	3237983278190077637062 59
111	4970201318407273887234 31
112	4401419508359845373802 81
113	0441454925246153530914 64
114	8650150502073624665324 94
115	6220682448547956388450 18
116	3726469460906848990021 12
117	3434153194693042280301 23
118	6548961628271198309149 57
119	4144353193084347698511 14

```
120   03123617281231722666997 3
121   46895905866527664055424 14
122   69228070786006049582008 2
123   56552514567401802500250 0
124   14186103388029565224152 2
125   16952878737475984171368 2
126   96174269166384276587255 2
127   82657196082018302303520 7
128   72131030480083002603965 6
129   69793700905070642821743 7
130   59020046879422611906727 9
131   11096213809771960698086 2
132   03663032496690897196368 1
133   27402183822083966625361 1
134   29825468872564558729497 8
135   45954659580786672391730 6
136   38015201455830126113099 5
137   93450953145683792841981 5
138   07861072795526998157500 8
139   33853676069125282694692 9
140   89318614358531434980332 0
141   46002948772861977031522 7
142   76642158020926208009584 8
143   95685394289679046368835 8
144   06585195259828863382467 0
145   77781448223101503748276 9
146   33203241854766118164231 2
147   27852769617624802195900 4
148   48228280806857222568376 0
149   04408494818038867520039 1
150   02435795653009010096642 7
151   76658103564359976888591 1
152   89219767607004952521408 8
153   52469476354425061878959 8
154   21769877935329990523092 1
155   33014304103349636714396 9
156   33218296288199895933337 4
157   93344909711250024072984 3
158   32379832781900776370625 9
159   49702013184072738872343 1
160   44014195083598453738028 1
161   04414549252461535309146 4
162   86501505020736246653249 4
163   62206824485479563884501 8
164   37264694609068489900211 2
165   34341531946930422803012 3
166   65489616282711983091495 7
167   41443531930843476985111 4
168   03123617281231722666997 3
169   46895905865276640554241 4
170   69228070786006049582008 2
171   56552514567401802500250 0
172   14186103388029565224152 2
173   16952878737475984171368 2
174   96174269166384276587255 2
175   82657196082018302303520 7
176   72131030480083002603965 6
177   69793700905070642821743 7
178   59020046879422611906727 9
179   11096213809771960698086 2
```


24<

180	036630324966908971963681
181	27402183822083966625361 1
182	29825468372564558729497 8
183	45954659580786672391730 6
184	38015201455830126113099 5
185	93450953145683792841981 5
186	078610727955269981575008
187	33853676069125282694692 9
188	89318614358531434980332 0
189	46002948772861977031522 7
190	76642158020926208009584 8
191	95685394289679046368835 8
192	06585195259828863382467 0
193	77781448223101503748276 9
194	33203241854766118164231 2
195	27852769617624802195900 4
196	48228280806857222568376 0
197	04408494818038867520039 1
198	02435795653009010096642 7
199	76658103564359976888591 1
200	89219767607004952521408 8
201	52469476354425061878959 8
202	21769877935329990523092 1
203	33014304103349636714396 9
204	33218296288199895933337 4
205	93344909711250024072984 3
206	32379832781900776370625 9
207	49702013184072738872343 1
208	44014195083598453738028 1
209	04414549252461535309146 4
210	86501505020736246653249 4
211	62206824485479563884501 8
212	37264694609068489900211 2
213	34341531946930422803012 3
214	65489616282711983091495 7
215	41443531930843476985111 4
216	03123617281231722666997 3
217	46895905865276640554241 4
218	69228070786006049582008 2
219	56552514567401802500250 0
220	14186103388029565224152 2
221	16952878737475984171368 2
222	96174269166384276587255 2
223	82657196082018302303520 7
224	72131030480008300260396 5 6
225	69793700905070642821743 7
226	59020046879422611906 7279
227	11096213809771960698086 2
228	03663032496690897196368 1
229	27402183822083966625361 1
230	29825468872564558729497 8
231	45954659580786672391730 6
232	38015201455830126113099 5
233	93450953145683792841981 5
234	07861072795526998157500 8
235	33853676069125282694692 9
236	89318614358531434980332 0
237	46002948772861977031522 7
238	76642158020926208009584 8
239	95685394289679046368835 8

25<

240 0658519525982886338246 70
241 77781448223101503748276 9
242 33203241854766118164231 2
243 27852769617624802195900 4
244 48228280806857222568376 0
245 04408494818038867520039 1
246 02435795653009010096642 7
247 76658103564359976888591 1
248 89219767607004952521408 8
249 52469476354425061878959 8
250 21769877935329990523092 1
251 33014304103349636714396 9
252 33218296288199895933337 4
253 93344909711250024072984 3
254 32379832781900776370625 9
255 49702013184072738872343 1
256 44014195083598453738028 1
257 04414549252461535309146 4
258 86501505020736246653249 4
259 62206824485479563884501 8
260 37264694609068489900211 2
261 34341531946930422803012 3
262 65489616282711983091495 7
263 41443531930843476985111 4
264 03123617281231722666997 3
265 46895905865276640554241 4
266 69228070786006049582008 2
267 56552514567401802500250 0
268 14186103388029565224152 2
269 16952878737475984171368 2
270 96174269166384276587255 2
271 82657196082018302303520 7
272 72131030480083002603965 6
273 69793700905070642821743 7
274 59020046879422611906727 9
275 11096213809771960698086 2
276 03663032496690897196368 1
277 27402183822083966625361 1
278 29825468872564558729497 8
279 45954659580786672391730 6
280 38015201455830126113099 5
281 93450953145683792841981 5
282 07861072795526998157500 8
283 33853676069125282694692 9
284 89318614358531434980332 0
285 46002948772861977031522 7
286 76642158020926208009584 8
287 95685394289679046368835 8
288 06585195259828863382467 0
289 77781448223101503748276 9
290 33203241854766118164231 2
291 27852769617624802195900 4
292 48228280806857222568376 0
293 04408494818038867520039 1
294 02435795653009010096642 7
295 76658103564359976888591 1
296 89219767607004952521408 8
297 52469476354425061878959 8
298 21769877935329990523092 1
299 33014304103349636714396 9

26<

300 3321829628819989593333374
301 93344909711250024072984 3
302 32379832781900776370625 9
303 49702013184072738872343 1
304 44014195083598453738028 1
305 04414549252461535309146 4
306 86501505020736246653249 4
307 62206824485479563884501 8
308 37264694609068489900211 2
309 34341531946930422803012 3
310 65489616282711983091495 7
311 41443531930843476985111 4
312 03123617281231722666997 3
313 46895905865276640554241 4
314 69228070786006049582008 2
315 5655251456740180250025 00
316 14186103388029565224152 2
317 16952878737475984171368 2
318 96174269166384276587255 2
319 82657196082018302303520 7
320 72131030480083002603965 6
321 69793700905070642821743 7
322 59020046879422611906727 9
323 11096213809771960698086 2
324 03663032496690897196368 1
325 27402183822083966625361 1
326 29825468872564558729497 8
327 45954659580786672391730 6
328 38015201455830126113099 5
329 93450953145683792841981 5
330 07861072795526998157500 8
331 33853676069125282694692 9
332 89318614358531434980332 0
333 46002948772861977031522 7
334 76642158020926208009584 8
335 95685394289679046368835 8
336 06585195259828863382467 0
337 77781448223101503748276 9
338 33203241854766118164231 2
339 27852769617624802195900 4
340 48228280806857222568376 0
341 04408494818038867520039 1
342 02435795653009010096642 7
343 76658103564359976888591 1
344 89219767607004952521408 8
345 52469476354425061878959 8
346 21769877935329990523092 1
347 33014304103349636714396 9
348 33218296288199895933337 4
349 93344909711250024072984 3
350 32379832781900776370625 9
351 49702013184072738872343 1
352 44014195083598453738028 1
353 04414549252461535309146 4
354 86501505020736246653249 4
355 62206824485479563884501 8
356 37264694609068489900211 2
357 34341531946930422803012 3
358 65489616282711983091495 7
359 41443531930843476985111 4

3o0	031236172812317226oo9973
3o1	468959058652766405542414
3o2	692280707860060495820082
3o3	565525145674018025002500
3o4	141861033880295652241522
3o5	169528787374759841713682
3oo	961742691663842765872552

Appendix B

```
      SUBROUTINE RUN(A,B,C,CHI,TX1,TX2,IDAY,ISC,RNG)                    RN000100
C         9/10/79                                                       RN000200
C*** THE FUNCTION OF THIS SUBROUTINE IS TO CALCULATE AND PRINT RUNNING  RN000300
C    AVERAGES FOR 3-HOUR, 8-HOUR AND/OR 24-HOUR AVERAGING TIMES. THIS   RN000400
C    PROCEDURE WAS DEVELOPED FOR USE WITH THE SINGLE SOURCE CRSTER      RN000500
C    MODEL. TO ESTABLISH THIS SUBROUTINE, ONE NEED ONLY ADD THE         RN000600
C    FOLLOWING CALL STATEMENTS TO THE CRSTER ROUTINES INDICATED BELOW:  RN000700
C                                                                       RN000800
C     MAIN CRSV                                                         RN000900
C                                                                       RN001000
C      CALL RUN(SOURCE(1),SOURCE(2),SOURCE(3),GADJ,TX1,TX2,DAY,ISC,RNG) RN001100
C      CALL RUN(SOURCE(1),SOURCE(2),SOURCE(3),GADJ,TX1,TX2,DAY,ISC,RNG) RN001200
C         AS LINES CV018150 AND CV027750 RESPECTIVELY.                  RN001300
C                                                                       RN001400
C     SUBROUTINE CRS                                                    RN001500
C                                                                       RN001600
C      CALL RUN(TX1,TX1,TX1,CHI,TX1,TX2,DAY,ISC,RNG)                    RN001700
C      CALL RUN(TX1,TX1,TX1,CHI,TX1,TX2,DAY,ISC,RNG)                    RN001800
C         AS LINES CR013750 AND CR071050 RESPECTIVELY.                  RN001900
C                                                                       RN002000
C                                                                       RN002100
C    TO OPTION THE USE OF THE SUBROUTINE, THE FIRST OF THE TWO BLANK    RN002200
C    CARDS AT THE VERY END OF THE CRSTER INPUT DECK IS USED. ANY        RN002300
C    CHARACTER IN CC 1-4 WILL PRODUCE 3-HOUR RUNNING AVERAGES; ANY      RN002400
C    CHARACTER IN CC 5-8 WILL PRODUCE 8-HOUR RUNNING AVERAGES; ANY      RN002500
C    CHARACTER IN CC 9-12 WILL PRODUCE 24-HOUR RUNNING AVERAGES. FOR    RN002600
C    EACH AVERAGING TIME CHOSEN, A HIGHEST, SECOND HIGHEST AND HIGH-50  RN002700
C    TABLE WILL BE PRINTED.                                             RN002800
C                                                                       RN002900
C                                                                       RN003000
C    THE SECOND HIGHEST RUNNING AVERAGES CALCULATED ARE DETERMINED      RN003100
C    USING THE PROCEDURE OUTLINED UNDER ISSUE 7B IN THE OAQPS GUIDELINE RN003200
C    DOCUMENT ENTITLED "GUIDELINES FOR THE INTERPRETATION OF AIR        RN003300
C    QUALITY STANDARDS, NO. 1.2-008 (REVISED FEBRUARY 1977)".           RN003400
C                                                                       RN003500
C                                                                       RN003600
C    RESTRICTIONS                                                       RN003700
C                                                                       RN003800
C       1) IF THE SOURCE CONTRIBUTION OPTION IN CRSTER IS TURNED        RN003900
C          ON (ISC=1), THE RUNNING AVERAGE OPTION WILL DEFAULT TO "OFF".RN004000
```

```
C                                                                       RN004100
C       2) ANY NUMBER OF DAYS OF THE YEAR MAY BE RUN FOR CRSTER IN      RN004200
C          CONJUNCTION WITH SUBROUTINE RUN BUT ALL OF THE DAYS SELECTED RN004300
C          MUST DEFINE A CONTINUOUS PERIOD OF DAYS (NO GAPS) IN ORDER   RN004400
C          FOR THE RUNNING AVERAGE RESULTS TO BE MEANINGFUL.            RN004500
C                                                                       RN004600
C                                                                       RN004700
C                                                                       RN004800
C                                                                       RN004900
C                                                                       RN005000
      DIMENSION CHI(180),TX1(6),TX2(2),PNG(5),IDAY(366)                 RN005100
      DIMENSION CONC(180),AVG3(180),AVG8(180),AVG24(180),               RN005200
     *AWK(180),IAWK(180),JAWK(180),HI503(51),IH503(51),ID503(51),       RN005300
     *HI508(51),IH508(51),ID508(51),HI524(51),                          RN005400
     *IH5024(51),ID5024(51),JMAX1U(180),DMAXUN(180),                    RN005500
     *TOT3(180),TOT8(180),TOT24(180),                                   RN005600
     *RTAB3(180,4),RTAB8(180,9),RTAB24(180,25),                         RN005700
     *ITID3(180,4),ITID8(180,9),ITID24(180,25),                         RN005800
     *VAL3(180,3),VAL8(180,8),VAL24(180,24),IUNI(180)                   RN005900
      INTEGER*2 SAB(180,2),SUB(36,5)                                    RN006000
      DATA AA,BB,CC /'  ','  ','  '/                                    RN006100
      DATA N,ID,IRA3,IRA8,IRA24 /5*0/                                   RN006200
      DATA SAB/36*1,36*2,36*3,36*4,36*5,                                RN006300
     *1,2,3,4,5,6,7,8,9,10,11,12,13,14,15,16,17,18,19,20,21,22,         RN006400
     *23,24,25,26,27,28,29,30,31,32,33,34,35,36,1,2,3,4,5,6,7,8,9,10,11,RN006500
     *12,13,14,15,16,17,18,19,20,21,22,23,24,25,26,27,28,29,30,31,32,33,RN006600
     *34,35,36,1,2,3,4,5,6,7,8,9,10,11,12,13,14,15,16,17,18,19,20,21,22,RN006700
     *23,24,25,26,27,28,29,30,31,32,33,34,35,36,1,2,3,4,5,6,7,8,9,10,11,RN006800
     *12,13,14,15,16,17,18,19,20,21,22,23,24,25,26,27,28,29,30,31,32,33,RN006900
     *34,35,36,1,2,3,4,5,6,7,8,9,10,11,12,13,14,15,16,17,18,19,20,21,22,RN007000
     *23,24,25,26,27,28,29,30,31,32,33,34,35,36/                        RN007100
      DATA SUB/1,2,3,4,5,6,7,8,9,10,11,12,13,14,15,16,17,18,19,20,21,22,RN007200
     *23,24,25,26,27,28,29,30,31,32,33,34,35,36,37,38,39,40,41,42,43,44,RN007300
     *45,46,47,48,49,50,51,52,53,54,55,56,57,58,59,60,61,62,63,64,65,66,RN007400
     *67,68,69,70,71,72,73,74,75,76,77,78,79,80,81,82,83,84,85,86,87,88,RN007500
     *89,90,91,92,93,94,95,96,97,98,99,100,101,102,103,104,105,106,107, RN007600
     *108,109,110,111,112,113,114,115,116,117,118,119,120,121,122,123,  RN007700
     *124,125,126,127,128,129,130,131,132,133,134,135,136,137,138,139,  RN007800
     *140,141,142,143,144,145,146,147,148,149,150,151,152,153,154,155,  RN007900
     *156,157,158,159,160,161,162,163,164,165,166,167,168,169,170,171,  RN008000
```

```
     *172,173,174,175,176,177,178,179,180/                                    RN0C8100
      IF(ISC.EQ.1)RETURN                                                      RN0C8200
      N=N+1                                                                   RN0C8300
      IF(N.EQ.2)RETURN                                                        RN0C8400
      IF(N.GT.2)GO TO 1000                                                    RN0C8500
      IF(A.NE.AA)IRA3=1                                                       RN0C8600
      IF(B.NE.BB)IRA8=1                                                       RN0C8700
      IF(C.NE.CC)IRA24=1                                                      RN0C8800
      DO 1 I=1,365                                                            RN0C8900
    1 ID=ID+IDAY(I)*24                                                        RN0C9000
      RETURN                                                                  RN0C9100
 1000 IF(IRA3.EQ.1.OR.IRA8.EQ.1.OR.IRA24.EQ.1) GO TO 2000                     RN0C9200
      RETURN                                                                  RN0C9300
 2000 IDD=N-3                                                                 RN0C9400
      IF(ID.EQ.IDD) GO TO 3000                                                RN0C9500
C                                                                             RN0C9600
C                                                                             RN0C9700
C                                                                             RN0C9800
C***COMMENCE CALCULATING RUNNING AVERAGES FOR SELECTED AVERAGING TIMES.       RN0C9900
C                                                                             RN0D0000
C                                                                             RN0D0100
C                                                                             RN0D0200
      DO 5 LR=1,180                                                           RN0D0300
      CONC(LR)=CHI(LR)                                                        RN0D0400
    5 CONTINUE                                                                RN0D0500
      ISUMR=ISUMR+1                                                           RN0D0600
      IF(IRA3.EQ.0)GO TO 40                                                   RN0D0700
C                                                                             RN0D0800
C***CALCULATE 3-HOUR RUNNING AVERAGES.                                        RN0D0900
C                                                                             RN0D1000
      IF(ISUMR.GE.3)GO TO 20                                                  RN0D1100
      DO 10 LR=1,180                                                          RN0D1200
      VAL3(LR,ISUMR+1)=CONC(LR)                                               RN0D1300
      TOT3(LR)=TOT3(LR)+CONC(LR)                                              RN0D1400
   10 CONTINUE                                                                RN0D1500
      GO TO 40                                                                RN0D1600
   20 DO 25 LR=1,180                                                          RN0D1700
      TOT3(LR)=TOT3(LP)-VAL3(LR,1)+CONC(LR)                                   RN0D1800
      AVG3(LR)=TOT3(LR)/3.                                                    RN0D1900
      DO 24 IO=1,2                                                            RN0D2000
```

```
      VAL3(LR,IQ)=VAL3(LR,IQ+1)                                          RN012100
   24 CONTINUE                                                           RN012200
      VAL3(LR,3)=CONC(LR)                                                RN012300
   25 CONTINUE                                                           RN012400
      DO 29 LR=1,180                                                     RN012500
      DO 28 IOUR=1,4                                                     RN012600
      IF(AVG3(LR).LT.RTAB3(LR,IOUR))GO TO 28                             RN012700
      IF(IOUR.EQ.4)GO TO 23                                              RN012800
      IP=4-IOUR                                                          RN012900
      DO 27 LTS=1,IP                                                     RN013000
      LS=5-LTS                                                           RN013100
      RTAB3(LR,LS)=RTAB3(LR,LS-1)                                        RN013200
      ITID3(LR,LS)=ITID3(LR,LS-1)                                        RN013300
   27 CONTINUE                                                           RN013400
   23 RTAB3(LR,IOUR)=AVG3(LR)                                            RN013500
      ITID3(LR,IOUR)=ISUMR-2                                             RN013600
      GO TO 29                                                           RN013700
   28 CONTINUE                                                           RN013800
   29 CONTINUE                                                           RN013900
      DO 45 LR=1,180                                                     RN014000
      DO 44 LT=1,50                                                      RN014100
      IF(AVG3(LR).LE.HI503(LT))GO TO 44                                  RN014200
      IF(LT.EQ.50)GO TO 47                                               RN014300
      IP=50-LT                                                           RN014400
      DO 43 LTS=1,IP                                                     RN014500
      LS=51-LTS                                                          RN014600
      HI503(LS)=HI503(LS-1)                                              RN014700
      IH503(LS)=IH503(LS-1)                                              RN014800
      ID503(LS)=ID503(LS-1)                                              RN014900
   43 CONTINUE                                                           RN015000
   47 HI503(LT)=AVG3(LR)                                                 RN015100
      IH503(LT)=ISUMR-2                                                  RN015200
      ID503(LT)=LR                                                       RN015300
      GO TO 45                                                           RN015400
   44 CONTINUE                                                           RN015500
   45 CONTINUE                                                           RN015600
   40 IF(IRA8.EQ.0)GO TO 70                                              RN015700
C                                                                        RN015800
C***CALCULATE 8-HOUR RUNNING AVERAGES.                                   RN015900
C                                                                        RN016000
```

```
      IF(ISUMR.GE.8)GO TO 50                                          RN016100
      DO 46 LR=1,180                                                  RN016200
      VAL8(LR,ISUMR+1)=CONC(LR)                                       RN016300
      TOT8(LR)=TOT8(LR)+CONC(LR)                                      RN016400
   46 CONTINUE                                                        RN016500
      GO TO 70                                                        RN016600
   50 DO 52 LR=1,180                                                  RN016700
      TOT8(LR)=TOT8(LR)-VAL8(LR,1)+CONC(LR)                           RN016800
      AVG8(LR)=TOT8(LR)/8.                                            RN016900
      DO 51 IQ=1,7                                                    RN017000
      VAL8(LR,IQ)=VAL8(LR,IQ+1)                                       RN017100
   51 CONTINUE                                                        RN017200
      VAL8(LR,8)=CONC(LR)                                             RN017300
   52 CONTINUE                                                        RN017400
      DO 60 LR=1,180                                                  RN017500
      DO 59 IOUR=1,9                                                  RN017600
      IF(AVG8(LR).LE.RTAB8(LR,IOUR))GO TO 59                          RN017700
      IF(IOUR.EQ.9)GO TO 57                                           RN017800
      IP=9-IOUR                                                       RN017900
      DO 58 LTS=1,IP                                                  RN018000
      LS=10-LTS                                                       RN018100
      RTAB8(LR,LS)=RTAB8(LR,LS-1)                                     RN018200
      ITID8(LR,LS)=ITID8(LR,LS-1)                                     RN018300
   58 CONTINUE                                                        RN018400
   57 RTAB8(LR,IOUR)=AVG8(LR)                                         RN019500
      ITID8(LR,IOUR)=ISUMR-7                                          RN018600
      GO TO 60                                                        RN018700
   59 CONTINUE                                                        RN018800
   60 CONTINUE                                                        RN018900
      DO 65 LR=1,180                                                  RN019000
      DO 64 LT=1,50                                                   RN019100
      IF(AVG8(LR).LE.HI508(LT))GO TO 64                               RN019200
      IF(LT.EQ.50)GO TO 67                                            RN019300
      IP=50-LT                                                        RN019400
      DO 63 LTS=1,IP                                                  RN019500
      LS=51-LTS                                                       RN019600
      HI508(LS)=HI508(LS-1)                                           RN019700
      IH508(LS)=IH508(LS-1)                                           RN019800
      ID508(LS)=ID508(LS-1)                                           RN019900
   63 CONTINUE                                                        RN020000
```

```
   67 HI508(LT)=AVG8(LR)                                                RN020100
      IH508(LT)=ISUMR-7                                                 RN020200
      ID508(LT)=LR                                                      RN020300
      GO TO 65                                                          RN020400
   64 CONTINUE                                                          RN020500
   65 CONTINUE                                                          RN020600
   70 IF(IRA24.EQ.0)GO TO 4081                                          RN020700
C                                                                       RN020800
C***CALCULATE 24-HOUR RUNNING AVERAGES.                                 RN020900
C                                                                       RN021000
      IF(ISUMR.GE.24)GO TO 71                                           RN021100
      DO 72 LR=1,180                                                    RN021200
      VAL24(LR,ISUMR+1)=CONC(LR)                                        RN021300
      TOT24(LR)=TOT24(LR)+CONC(LR)                                      RN021400
   72 CONTINUE                                                          RN021500
      GO TO 4081                                                        RN021600
   71 DO 74 LR=1,180                                                    RN021700
      TOT24(LR)=TOT24(LR)-VAL24(LR,1)+CONC(LR)                          RN021800
      AVG24(LR)=TOT24(LR)/24.                                           RN021900
      DO 73 IQ=1,23                                                     RN022000
      VAL24(LR,IQ)=VAL24(LR,IQ+1)                                       RN022100
   73 CONTINUE                                                          RN022200
      VAL24(LR,24)=CONC(LR)                                             RN022300
   74 CONTINUE                                                          RN022400
      DO 80 LR =1,180                                                   RN022500
      DO 79 IOUR=1,25                                                   RN022600
      IF(AVG24(LR).LE.RTAB24(LR,IOUR))GO TO 79                          RN022700
      IF(IOUR.EQ.25)GO TO 75                                            RN022800
      IP=25-IOUR                                                        RN022900
      DO 78 LTS=1,IP                                                    RN023000
      LS=26-LTS                                                         RN023100
      RTAB24(LR,LS)=RTAB24(LR,LS-1)                                     RN023200
      ITID24(LR,LS)=ITID24(LR,LS-1)                                     RN023300
   78 CONTINUE                                                          RN023400
   75 RTAB24(LR,IOUR)=AVG24(LR)                                         RN023500
      ITID24(LR,IOUR)=ISUMR-23                                          RN023600
      GO TO 80                                                          RN023700
   79 CONTINUE                                                          RN023800
   80 CONTINUE                                                          RN023900
      DO 85 LR=1,180                                                    RN024000
```

```
      DO 84 LT=1,50                                                          RN024100
      IF(AVG24(LR).LE.HI5024(LT)) GO TO 84                                   RN024200
      IF (LT.EQ.50)GO TO 87                                                  RN024300
      IP=50-LT                                                               RN024400
      DO 83 LTS=1,IP                                                         RN024500
      LS=51-LTS                                                              RN024600
      HI5024(LS)=HI5024(LS-1)                                                RN024700
      IH5024(LS)=IH5024(LS-1)                                                RN024800
      ID5024(LS)=ID5024(LS-1)                                                RN024900
   83 CONTINUE                                                               RN025000
   87 HI5024(LT)=AVG24(LR)                                                   RN025100
      IH5024(LT)=ISUMR-23                                                    RN025200
      ID5024(LT)=LR                                                          RN025300
      GO TO 85                                                               RN025400
   84 CONTINUE                                                               RN025500
   85 CONTINUE                                                               RN025600
      RETURN                                                                 RN025700
C                                                                            RN025800
C                                                                            RN025900
C                                                                            RN026000
C***COMMENCE WRITING OUTPUT TABLES FOR SELECTED AVERAGEING TIMES.            RN026100
C                                                                            RN026200
C                                                                            RN026300
C                                                                            RN026400
 3000 IF(IRA24.EQ.0)GO TO 9135                                               RN026500
      INM=24                                                                 RN026600
 9101 CONTINUE                                                               RN026700
C                                                                            RN026800
C***TRANSFER 24-HOUR TABLES FOR PRINTING.                                    RN026900
C                                                                            RN027000
      DO 9100 LR=1,180                                                       RN027100
      DO 9105 J=1,INM                                                        RN027200
      K=J+1                                                                  RN027300
 9103 K=K-1                                                                  RN027400
      IF(K.EQ.0)GO TO 9105                                                   RN027500
      IF((ABS(ITID24(LR,K)-ITID24(LR,J+1))).LT.INM)GO TO 9103                RN027600
      RTAB24(LR,2)=RTAB24(LR,J+1)                                            RN027700
      ITID24(LR,2)=ITID24(LR,J+1)                                            RN027800
      GO TO 9100                                                             RN027900
 9105 CONTINUE                                                               RN028000
```

```
 9100 CONTINUE                                                          RN028100
C                                                                       RN028200
C***GENERALIZED ROUTINE TO PREPARE **HIGHEST** TABLES FOR EACH          RN028300
C    AVERAGING TIME FOR PRINTING.                                       RN028400
C                                                                       RN028500
      DO 9110 LR=1,180                                                  RN028600
      AWK(LR)=RTA924(LR,1)                                              RN028700
      IAWK(LR)=ITID24(LR,1)/24                                          RN028800
      IWK=IAWK(LR)*24                                                   RN028900
      JAWK(LR)=ITID24(LR,1)-IWK                                         RN029000
      IAWK(LR)=IAWK(LR)+1                                               RN029100
      IF(JAWK(LR).EQ.0)JAWK(LR)=24                                      RN029200
      IF(JAWK(LR).EQ.0)IAWK(LR)=IAWK(LR)-1                              RN029300
 9110 CONTINUE                                                          RN029400
      IJN=0                                                             RN029500
      DO 9106 IJER=1,36                                                 RN029600
      DO 9106 IJES=1,5                                                  RN029700
      IJN=IJN+1                                                         RN029800
      IJK=SUB(IJER,IJES)                                                RN029900
      DMAXUN(IJN)=AWK(IJK)                                              RN030000
      JMAX1U(IJN)=IAWK(IJK)                                             RN030100
      IUNI(IJN)=JAWK(IJK)                                               RN030200
 9106 CONTINUE                                                          RN030300
C                                                                       RN030400
C***GENERALIZED ROUTINE FOR PRINTING **HIGHEST** TABLES FOR EACH        RN030500
C    AVERAGING TIME.                                                    RN030600
C                                                                       RN030700
      WRITE(6,6050)TX1,TX2                                              RN030800
 6050 FORMAT(1H1,2X,'PLANT NAME: ',6A4,'  POLLUTANT: ',2A4,             RN030900
     *'  EMISSION UNITS: GM/SEC  ','  AIR QUALITY UNITS: GM/M**3'/)     RN031000
      WRITE(6,9080)INM,RNG                                              RN031100
 9080 FORMAT(1X,T17,'HIGHEST ',I2,'-HOUR RUNNING AVERAGE',              RN031200
     *' CONCENTRATIONS AT EACH RECEPTOR'//                              RN031300
     *1X,T4,'RANGE   ',4(F5.1,' KM',17X),F5.1,' KM'/                    RN031400
     *1X ,T2,'DIR'/3X,5(14X,'(DAY,ST HR)'))                            RN031500
      DO 9120 I=1,36                                                    RN031600
      IFR=I*5-4                                                         RN031700
      ITO=I*5                                                           RN031800
      WRITE(6,8040)I,(DMAXUN(J),JMAX1U(J),IUNI(J),J=IFR,ITO)           RN031900
 8040 FORMAT(1X,T3,I2,T6,5(1PE11.4,' (',I3,',',I2,')',5X))              RN032000
```

```
 9120 CONTINUE                                                          RN032100
C                                                                       RN032200
C***GENERALIZED ROUTINE FOR PREPARING **SECOND HIGHEST** TABLES FOR     RN032300
C    EACH AVERAGING TIME FOR PRINTING.                                  RN032400
C                                                                       RN032500
      DO 9122 LR=1,180                                                  RN032600
      AWK(LR)=RTAB24(LR,2)                                              RN032700
      IAWK(LR)=ITID24(LR,2)/24                                          RN032800
      IWK=IAWK(LR)*24                                                   RN032900
      JAWK(LR)=ITID24(LR,2)-IWK                                         RN033000
      IAWK(LR)=IAWK(LR)+1                                               RN033100
      IF(JAWK(LR).EQ.0)JAWK(LR)=24                                      RN033200
      IF(JAWK(LR).EQ.0)IAWK(LR)=IAWK(LR)-1                              RN033300
 9122 CONTINUE                                                          RN033400
      IJN=0                                                             RN033500
      DO 9104 IJER=1,36                                                 RN033600
      DO 9104 IJES=1,5                                                  RN033700
      IJN=IJN+1                                                         RN033800
      IJK=SUB(IJER,IJES)                                                RN033900
      DMAXUN(IJN)=AWK(IJK)                                              RN034000
      JMAX1U(IJN)=IAWK(IJK)                                             RN034100
      IUNI(IJN)=JAWK(IJK)                                               RN034200
 9104 CONTINUE                                                          RN034300
C                                                                       RN034400
C***GENERALIZED ROUTINE FOR PRINTING **SECOND HIGHEST** TABLES FOR      RN034500
C    EACH AVERAGING TIME.                                               RN034600
C                                                                       RN034700
      WRITE(6,6050)TX1,TX2                                              RN034800
      WRITE(6,9081)INM,RNG                                              RN034900
 9081 FORMAT(1X,T17,'SECOND HIGHEST ',I2,'-HOUR RUNNING AVERAGE',       RN035000
     *' CONCENTRATIONS AT EACH RECEPTOR'//                               RN035100
     *1X,T4,'RANGE    ',4(F5.1,' KM',17X),F5.1,' KM'/                   RN035200
     *1X ,T2,'DIR'/3X,5(14X,'(DAY,ST HR)'))                             RN035300
      DO 9123 I=1,36                                                    RN035400
      IFR=I*5-4                                                         RN035500
      ITO=I*5                                                           RN035600
      WRITE(6,8040)I,(DMAXUN(J),JMAX1U(J),IUNI(J),J=IFR,ITO)            RN035700
 9123 CONTINUE                                                          RN035800
      WRITE(6,9128)                                                     RN035900
 9128 FORMAT(//////58X,'**** NOTE ****'//                               RN036000
```

```
     *22X,'THE SECOND HIGHEST RUNNING AVERAGES LISTED ON THIS PAGE',     RN036100
     *' HAVE BEEN DETERMINED USING THE'/                                 RN036200
     *21X,' PROCEDURE OUTLINED UNDER ISSUE 7B IN THE OAQPS GUIDE',      RN036300
     *'LINE DOCUMENT ENTITLED GUIDELINES'/                              RN036400
     *22X,'FOR THE INTERPRETATION OF AIR QUALITY STANDARDS,',           RN036500
     *' NO. 1.2-008 (REVISED FEBRUARY 1977).')                          RN036600
C                                                                       RN036700
C***GENERALIZED ROUTINE FOR PREPARING **HIGH-50** TABLES FOR EACH       RN036800
C    AVERAGING TIME FOR PRINTING.                                       RN036900
C                                                                       RN037000
      WRITE(6,6050)TX1,TX2                                              RN037100
      WRITE(6,9129)INM,INM                                              RN037200
 9129 FORMAT(49X,'MAXIMUM ',I2,'-HOUR RUNNING AVERAGE',                 RN037300
     *' CONCENTRATIONS'//                                               RN037400
     *41X,'DAY     ',I2,'-HOUR RUNNING AVG    DIRECTION    ',         RN037500
     *'DISTANCE  START HOUR'/)                                          RN037600
      DO 9132 I=1,50                                                    RN037700
      KR2=IH5024(I)/24                                                  RN037800
      IWK=KR2*24                                                        RN037900
      KR7=IH5024(I)-IWK                                                 RN038000
      KR2=KR2+1                                                         RN038100
      IF(KR7.EQ.0)KR7=24                                                RN038200
      IF(KR7.EQ.0)KR2=KR2-1                                             RN038300
      IWK=ID5024(I)                                                     RN038400
      KR4=SAB(IWK,1)                                                    RN038500
      GR5=RNG(KR4)                                                      RN038600
      KR4=SAB(IWK,2)                                                    RN038700
C                                                                       RN038800
C***GENERALIZED ROUTINE FOR PRINTING **HIGH-50** TABLES FOR EACH        RN038900
C    AVERAGING TIME.                                                    RN039000
C                                                                       RN039100
 9132 WRITE(6,9130)KR2,HI5024(I),KR4,GR5,KR7                            RN039200
 9130 FORMAT(40X,I3,1PE20.4,I14,0PF14.2,7X,I3)                          RN039300
 9135 IF(IRA8.EQ.0)GO TO 9160                                           RN039400
      IRA8=0                                                            RN039500
      INM=8                                                             RN039600
C                                                                       RN039700
C***TRANSFER 8-HOUR TABLE FOR PRINTING.                                 RN039800
C                                                                       RN039900
      DO 9136 I=1,50                                                    RN040000
```

```
      HI5024(I)=HI508(I)                                                RN040100
      IH5024(I)=IH508(I)                                                RN040200
      ID5024(I)=ID508(I)                                                RN040300
 9136 CONTINUE                                                          RN040400
      DO 9200 I=1,180                                                   RN040500
      DO 9200 J=1,9                                                     RN040600
      RTAB24(I,J)=RTAB8(I,J)                                            RN040700
      ITID24(I,J)=ITID8(I,J)                                            RN040800
 9200 CONTINUE                                                          RN040900
      GO TO 9101                                                        RN041000
 9160 IF(IRA3.EQ.0)GO TO 9260                                           RN041100
      IRA3=0                                                            RN041200
      INM=3                                                             RN041300
C                                                                       RN041400
C***TRANSFER 3-HOUR TABLES FOR PRINTING.                                RN041500
C                                                                       RN041600
      DO 9137 I=1,50                                                    RN041700
      HI5024(I)=HI503(I)                                                RN041800
      IH5024(I)=IH503(I)                                                RN041900
      ID5024(I)=ID503(I)                                                RN042000
 9137 CONTINUE                                                          RN042100
      DO 9230 I=1,180                                                   RN042200
      DO 9230 J=1,4                                                     RN042300
      RTAB24(I,J)=RTAB3(I,J)                                            RN042400
      ITID24(I,J)=ITID3(I,J)                                            RN042500
 9230 CONTINUE                                                          RN042600
      GO TO 9101                                                        RN042700
 9260 CONTINUE                                                          RN042800
 4081 RETURN                                                            RN042900
      END                                                               RN043000
```

December 1980

ADDENDUM/SUPPLEMENTAL INFORMATION

TO THE

INDUSTRIAL SOURCE COMPLEX (ISC) DISPERSION MODEL

The computer code modifications addressed herein are the complete set of changes made to date to the ISC code as it appears in the Industrial Source Complex (ISC) Dispersion Model User's Guide, Volume II, EPA-450/4-79-031, December 1979. All modifications have been incorporated in the ISC code as part of the UNAMAP-4 available from the National Technical Information Service (NTIS).

Each item in this report is preceded by the date on which it was issued.

A. Computer Program Modifications

Program modifications are described below. The changes correct errors in the original source code released in December 1979.

INDUSTRIAL SOURCE COMPLEX (ISCST) PROGRAM

Make the following modifications to Appendix A of the User's Guide and check your program for conformance.

1. 4/80 - Change the following lines of code in subroutine MODEL to read as follows:

```
IYR=YR                                          S0304630
YRS=SINNUM(IYR)                                 S0304640
YRC=COSNUM(IYR)                                 S0304650
IYR=YR                                          S0304800
YRS=SINNUM(IYR)                                 S0304810
YRC=COSNUM(IYR)                                 S0304820
```

2. 4/80 - Delete subroutine UPWIND from the ISC Short Term model program.

   Subroutine UPWIND was originally placed in the ISCST to save computer time by not calculating concentrations at polar coordinate receptors upwind of centrally located sources. However, due to an error in the subroutine, it was incorrectly applied to source/receptor combinations not covered by the original definition and as a result provided substantial but erroneous savings in computer run time. Correcting the subroutine though, has resulted in only a negligible savings in run time. Since subroutine MODEL provides an in-line upwind check for all source/receptor combinations and the computer time saved using the corrected UPWIND subroutine is negligible, the subroutine is being deleted.

3. 4/80 - Change the following line of code in subroutine MAXOT to read as follows:

```
      IY=(K-1)/NXPNTS+1                                                S0500370
```

4. 12/80 - Change the following lines of code in subroutine MODEL to read:

```
1010 IF(ISW(4).NE.1.OR.HS+ZS-GRIDZ(IJ).GT.0.0.OR.ITYPE.EQ.2)GO TO 1020  S0304930
     IF(ITYPE.GT.0)GO TO 1095                                           S0305200
     IF(VS.LE.0.0)GO TO 1095                                            S0305220
1095 IF(ISW(4).NE.1.OR.ISW(1).NE.1.OR.NVS.NE.0.OR.ITYPE.EQ.2)GO TO 1100 S0305480
```

These modifications are required to allow for the treatment of area sources as flat terrain sources as indicated in the documentation.

5. 12/80 - Insert the following line of code in subroutine MODEL:

```
      IF(I.EQ.1) JDY=JDAY                                               S0301795
```

12/80 - Delete line S0301930 from subroutine MODEL.

The modifications correct on error in the Julian Day for the selection of the meteorological card input data/no listing option.

6. 12/80 - Delete line S0306540 from subroutine MODEL.

12/80 - Insert the following line of code in subroutine MODEL:

```
      DO 1290 K=1,NVS                                                   S0306515
```

These modifications are necessary to eliminate the possibility of calculating an incorrect Vertical Term when ground-level concentrations are calculated from sources with significant gravitational settling.

7. 12/80 - Change the following lines of code in subroutine MODEL to read:

```
C     TEST FOR WAKE EFFECTS - CALCULATE XPLUME.                          S0304070
 780 DHA=3.*FM*GAMJI*UBARI*SSI                                          S0304110
```

12/80 - Insert the following line of code in subroutine MODEL:

```
      IF(1.570796327*UBARS*SSI.GT.HB+HB)DHA=DHA*SIN(S3*(HB+HB)*UBARI)   S0304115
```

12/80 - Delete line S0304170 from subroutine MODEL.

The modifications are required to correct a wake effects test plume rise calculation error.

INDUSTRIAL SOURCE COMPLEX (ISCLT) PROGRAM

Make the following program line modifications to Appendix B of the User's Guide and check your program for conformance.

1. 4/80 - Change the following line of code in subroutine MODEL to read:

```
IF (RD.GE.XMX) GO TO 1930                                    S0211230
```

This change allows sources located 100 m from a receptor to be considered for contribution to the receptor. This is compatible with the ISC Short Term Model.

2. 12/80 - Change the following line of code in subroutine MODEL to read:

```
IF(ZP.LT.ZS.OR.TYPE.EQ.2)ZP=ZS                               S0211150
```

This modification is required to allow for the treatment of area sources as flat terrain sources as indicated in the documentation.

3. 12/80 - Change the following line of code in subroutine MODEL to read:

```
IF(TYPE.NE.0.OR.JTYPE.EQ.0.OR.XB.GE.HB10)GO TO 1970          S0211740
```

This modification corrects a mis-coded switch used in the calculation of σ_z for stacks with wake effects and calculation distances less than 10 building heights.

4. 12/80 - Change the following line of code in subroutine OUTPT to read:

```
IF(NOCOMB(NG).EQ.1.AND.IDSORC(NGT+1).GE.0)GO TO 260           S0301621
```

This modification is required to correct an error that allowed the print output for an individual source to be printed several times.

5. 12/80 - Change the following lines of code in subroutines OUTPT and HEADNG respectively to read:

```
COMMON /HEAD/ MSG3(4),MSG4(8),IS,N3,I3,M3,ILN,LSTILN         S0300120
COMMON /HEAD/ MSG3(4),MSG4(8),IS,N3,I3,M3,ILN,LSTILN         S0400110
```

B. 4/80 - Computer Underflow in the Short Term and Long Term Model Programs

An underflow interrupt condition occurs on computers whenever an arithmetic operation between two very small numbers results in a number too small to be contained in the computer's arithmetic results register. When this condition arises, computers such as the UNIVAC 1100 series and the CDC 6000 series set the underflow result to zero and continue processing. The ISC model programs were specifically designed to allow the computer to zero an underflow condition, therefore an underflow condition is not to be considered an error within the ISC programs.

However, some IBM computers abort the run when an underflow occurs. In order to circumvent this problem the user must inform the computer system that underflows are to be set to zero and program execution to continue. For example, the following FORTRAN call may be inserted at the beginning of either ISC Model program and thus preclude termination of runs due to underflows on an IBM 360 series computer:

```
CALL ERRSET (208,256,-1,1,0,208)
```

To find the appropriate solution to this problem on other computer systems, the user should contact on-site systems personnel.

C. 4/80 - Receptor Heights Versus Source Elevations

The ISC model allows each receptor to be situated at any height (z). Both the ISCST and ISCLT programs terminate, however, if the receptor elevation is above the lowest source height. In addition, if any receptor is located below the source base height, the ISC programs automatically reset the receptor height to the source base height (thus, flat terrain is assigned for that source receptor combination). This will cause a receptor to be located at different vertical points if two or more sources affect the same receptor, and are at different base elevations. To avoid this problem all sources should be located at approximately the same base elevation, thus maintaining a consistent correction among receptors that are below the plane of the sources.

The rationale for the above suggestion stems from the applicability of the ISC model primarily to very localized industrial sources and complexes, i.e., the sources are not located in radically different locations or terrain. The model can be used for widely dispersed sources, but the user's decision to assume similar source elevations should be an explicit one.

D. Text Corrections to the User's Guide

Volume I

1. 4/80 - All discussion and figures pertaining to the subroutine UPWIND are to be disregarded.

2. 12/80 - Page 3-6, Receptor Grid System Option. Delete sentence 3 and replace it with:

3. 12/80 - Page 2-24. The exponential term in Equation (2-12) should be:

$$\exp\left[-\frac{1}{2}\left(\frac{y}{\sigma_y}\right)^2\right]$$

Additionally, a "3" value will automatically generate a grid system using the Cartesian coordinate system and a "4" value will automatically generate the polar coordinate direction radials with user-defined starting locations and spacing distances.

4. 12/80 - Page 3-42, Table 3-4. Line 10 in the Description which pertains to ISW(2), should be changed such that the line reads:

   4= program generates polar coordinate grid direction radials

5. 4/80 - Page 3-60. Add to equation (3-1) the term "+D".

6. 4/80 - Page 3-61. To the list of variables and their definitions add:

   D=NPNTS if ISW(4) equals "1" in the first card of Card Group (2); otherwise A equals "0".

7. 12/80 - Page 4-10. Equation (4-1) should be changed to read:

   $$\left.\begin{array}{l} J = 300 \\ \text{and} \\ I = \dfrac{(E-(N_x + N_y + 2\cdot N_{xy}) - K - L - M)}{(N_{se}\cdot(N_x\cdot N_y + N_{xy}))} \end{array}\right\} \quad (4\text{-}1)$$

8. 12/80 - Page 4-11, lines 9 and 11. References to "N_s" should be changed to "N_{se}".

9. 12/80 - Page 4-11. To the list of variables and their definitions add:

   $$M = \begin{cases} 0 \text{ ; if ISW(4)=1 \& ISW(11)=2 or} \\ \quad \text{if ISW(7)=1 or NSEASN=1 or NGROUP=0} \\ N_x\cdot N_y + N_{xy} \text{; if ISW(4)=0 or ISW(11)}\neq 2 \text{ \&} \\ \quad \text{if ISW(7)}\neq 1 \text{ \& NGROUP}\neq 0 \text{ \& NSEASN}\neq 1 \end{cases}$$

10. 12/80 - Page 4-16. Equation (4-2) should be changed to read the same as equation (4-1).

11. 12/80 - Page 4-17, equation (4-3). Reference to "N_s" should be changed to "N_{se}".

12. 12/80 - Page 4-77. Equation (4-4) should be changed to read:

    $$\left.\begin{array}{l} J = 300 \\ \text{and} \\ I = \left[\dfrac{E - (NXPNTS+NYPNTS+2*NXWYPT) - K - L - M}{NSEASN*(NXPNTS*NYPNTS+NXWYPT)}\right] \end{array}\right\} \quad (4\text{-}4)$$

B299/16

13. 12/80 - Page 4-78. To the list of variables and their definitions under "Condition c" add:

$$M = \begin{cases} 0 \text{ ; if ISW(4)=1 \& ISW(11)=2 or} \\ \quad \text{if ISW(7)=1 or NSEASN=1 or NGROUP=0} \\ NXPNTS*NYPNTS+NXWYPT; \text{ if ISW(4)=0 or ISW(11)}\neq 2 \text{ \&} \\ \quad \text{if ISW(7)=1 \& NSEASN=1 \& NGROUP=0} \end{cases}$$

14. 12/80 - Page 4-79. Equation (4-5) should be changed to read the same as equation (4-4).

15. 12/80 - Page 4-80. Delete variable "L" and replace it with:

"where L and M are the same as under Equation (4-4)".

Volume II

1. 4/80 - All discussion and figures pertaining to subroutine UPWIND are to be disregarded.

2. 4/80 - Page C-4, Figure C-1. The zero in card column 59 in the first card should be changed to a "6" such that the data value reads "860".

3. 4/80 - Page C-8, Figure C-1. The data in card columns 8 and 9 are to be transferred to columns 9 and 10 respectively with column 8 becoming blank. The change should be made for each of the 16 cards illustrated.

4. 4/80 - Page D-8, Figure D-1. The zero in card column 25 on the fourth last card should be changed to a "6" such that the data value reads ".0076794".

5. 4/80 - Page C-19, paragraph 1. Delete sentence 3 and replace it with:

Also, because ISW(15), ISW(17), and ISW(18) equal "1" and ISW(4) equals "0", variables A,B,C, and D become 425 times 5(or 2125), 4 times 1 times 425 times 5(or 8500), 201 times 1 times 5(or 1005), and 0, respectively, according to their definitions given in equation (3-1).

6. 4/80 - Page C-19. Add to equation (C-2):

variable version - "+D"
numerical interpretation - "+0"

7. 12/80 - Page D-24. The numerical solution in equation (D-3) should be changed to read:

$$40000 \geq 19+19+2\cdot 1 + (2\cdot 1+0)\cdot(19\cdot 19+1)$$

$$\geq 764$$